

**features:**

cross linked polyolefin  
 flame retardant  
 operating temp -55°C to + 125°C  
 Shrink ratio 3/1 up to 39/13  
 Green yellow shrink ratio 2/1  
 RoHS compliant

**std black and colors**

art code	D*	d*	w*	M/spool
TWM1.5/0.5	1,6	0,5	0,45	150
TWM3/1	3,2	1	0,55	150
TWM4.5/1.5	4,8	1,5	0,6	75
TWM6/2	6,4	2	0,65	75
TWM9/3	9,5	3	0,75	75
TWM12/4	12,7	4	0,8	50
TWM18/6	19,1	6	0,9	30
TWM24/8	25,4	8	1	30
TWM39/13	39	13	1,25	30
TWM50.8/25.4 (ratio 2/1)	50	26	1,14	30
TWM76.2/38.1 (ratio 2/1)	76	38	1,27	30

Up to shrink ratio 150/76 available on request

**Green yellow**

art code	D*	d*	w*	M/spool
TWM1.6/0.8GY	1,6	0,8	0,4	150
TWM2.4/1.2GY	2,4	1,2	0,48	150
TWM3.2/1.6GY	3,2	1,6	0,48	150
TWM4.8/2.4GY	4,8	2,4	0,48	75
TWM6.4/3.2GY	6,4	3,2	0,56	75
TWM9.5/4.8GY	9,5	4,8	0,62	75
TWM12.7/6.4GY	12,7	6,4	0,62	50
TWM19.1/9.5GY	19,1	9,5	0,68	30
TWM25.4/12.7GY	25,4	12,7	0,87	30
TWM38.1/19.0GY	38,1	19	1	30

D\* inner Ø as supplied, d\* inner Ø fully recovered, w\* wall thickness after fully recovered (mm)

**ordering info**

std color : Black

colors: Red, blue, Yellow, Green, White, Clear (non flame retardant) special colors on request

For colors add the color after product code. Example: **TWM12/4-RED**

**Packaging info**

std on spools